

MARKET LEADING PERFORMANCE

HIGHEST QUALITY COMPONENTS


Excellent Heat Management

Plug & Play Kits

CUSTOM INSTALL SYSTEMS

Full Range of Optics

THE PROFESIONAL'S CHOICE



Delivering excellent light to every state in The United States of America



DM Light Engine

- 288 Samsung LM561C midpower LED's powered under 150 mA.
- Custom extruded alumninum heat sink.
- Shoebox Fixtures
- Car Dealerships
- Bell Street Lights
- TUNNEL LIGHTS
- FLOOD LIGHTS
- SIGN LIGHTERS



DMZ Light Engine

- 32 Seoul hipower LED's
- powered at ~700mA



Meanwell HLG Driver Series

- 120-277 or 480 VAC
- 0-10V Dim to Off Potted
- Industry Leading Quality

- Streetlights
- BELL HOUSING
- Cylinder Shoebox
- Warehouse/Gymnasium
- TENNIS COURTS
- INDOOR TENNIS COURT UPLIGHT

<u>Any Installation</u> 175 Watt to 1000 Watt Replacement

hilumzusa.com



PERFORMANCE SPECIFICATIONS

Product	Size	Tested Input Wattage	Replaces	Delivered Lumens	Optics	Typical Height	CRI
DM60		57	200 - 250 Watts	8,820	N/A	15-25 ft	
DM80		76	250 - 300 Watts	11,500	N/A	15-25 ft	
DM100	Single Head	96	250-400 Watts	13,100	N/A	18-30 ft	
DM120		116	300 - 400 Watts	18,390	N/A	20-30 ft	80+
DM150		149	400 - 500 Watts	22,800	N/A	25-35 ft	
DM240	Dual	232	600 - 1000 Watts	36,600	N/A	30-40 ft	
DM300	Head	284	1000-1200 Watts	45,600	N/A	35-50 ft	
DMZ150	Single	139	300 - 400 Watts	15,200	T3, T5	25-35 ft	70.
DMZ300	Dual	278	750 - 1000 Watts	30,400	T3, T5	35-50 ft	70+

DMZ Light Unit available with a full range of optics

See seperate specification sheet for 30/50

Watt DC units, Wall Pack Cartridge, and

custom application specific solutions

Product	Length	Width	Height
Driver	9.0"	2.7"	1.5"
Single Head	6.0"	4.5"	3.0"
Dual Head	6.0"	10.0"	3.0"

Each light engine weights 2.4 lbs

ORDERING


EXAMPLE DM150-5080-1N-V: 150 Watt unit at 5000K with 120-277V dimmable driver and vertical FlexMount kit

Product	Cc	olor / CR	Ι	Driver	_	Mounting	1	Optics
<u>DM</u> DM60		<u>DM</u> 5080	_	1N = 120-277v 1D = 120-277v dim	-	<u>SOCKET MOUNT</u> H = FlexMount, Horizontal Socket	_	Blank (none)
DM80	1 1	4080		2N = 480v		V = FlexMount, Vertical Socket		DMZ Only_
DM120		3080		$2D = 480v \dim$		VS = Vertical Mount E39 Screw In		T3
DM150 DM240	1 1	DMZ				AD = Glass Adhesive Mount		T5 25°
DM300		5070 4070				Single Head Plates		78°
<u>DMZ</u> DMZ150		2770				FR = Plate Round Single Head FS = Plate Square Single Head		IP - Requires IP Protection*
DMZ300						FRD = Plate Round w/ Driver Mount FSD = Plate Square w/ Driver Mount		Surge
						DUAL HEAD PLATES FR = Plate Round FS = Plate Square FRD = Plate Round w/ Driver Mount FSD = Plate Square w/ Driver Mount		Blank (none) S277 = 120v-277v 10kV S480 = 480v 10kV
						CSTM = Custom		





MOUNTING



CONTROLS OPTIONS

- Motion Controls
- Wireless Solutions
- Surge Protection
- Step Down Transformers





Contact the HiLumz team to discuss integration