



**OVERVIEW**

**4,000 to 15,000 Lumen System  
Decorative & Industrial  
Indoor/Outdoor Application**

Integrated, serviceable, customizable, and tough LED light system for a variety of post top, garage, street light, and decorative lantern style fixtures. Easily customizable installation bases, downward angled light engines to optimize surface foot

candles and a serviceable and separate driver system to maximize operating life.



BOTTOM UP MOUNT

TOP DOWN MOUNT

**FEATURES**

- Socket mount or direct mount
- Experienced conversion kits for all major brands
- 0-10V dimming / Dali
- HiLumz mounting expertise
- House-Side / Street-Side directional
- 3,000 to 14,000 lumens
- Amber, 22k, 27k, 30k, 35k, 40k, 50k



**ORDERING**

**EXAMPLE HLPTK-50-U-40K-SM-T-PT1-SP:** 50 watt unit at 4000K, 80 CRI with Bottom Up Plate Mount, 360°, 10kV Surge

Product	Wattage	Input Voltage	Color/CCT	Directional Lighting	Light Angle
HLPTK	30 50 60 90 120	U = 100-277VAC H = 480VAC	50K = 5000K 40K = 4000K 35K = 3500K 30K = 3000K 27K = 2700K 22K = 2200K AM = Amber	SM = Symmetric (360°) ASM = Asymmetric (180°)	S = Straight T = Downward Tilt
				<b>Mounting</b> PT1 = Bottom Up Plate BE26 = Bottom Up E26 BE39 = Bottom Up E39 PT2 = Top Down Plate TE26 = Top Down E26 TE39 = Top Down E39 9XXXX = 5-digit Custom Mount CSTM = Custom (contact HiLumz)	<b>Controls</b> PC3 = 3-Pin Photocell PC7 = 7-Pin Photocell D = Dali Enabled PC7D = 7-Pin + Dali  <b>Surge</b> SP10 = 10kV Surge SP20 = 20kV Surge